

SUV 600

Specialist Utility Vehicle


SPECIFICATION SHEET



The all-new Specialist Utility Vehicle 600 (SUV 600) has taken a production standard Land Rover Discovery 4x4 and adapted it for use in the Emergency Services and wider utility sectors.

The additional third axle increases the payload capacity and the physical space on offer to allow heavier and larger systems to be fitted in order to broaden the usability of the vehicle. The SC Innovation SUV 600 offers an up to date, capable, efficient and cost-effective solution to operators of specialist and utility vehicle fleets who have a specific requirement that cannot be met by existing off-the-shelf utility vehicles. Operators will benefit from the delivery of an up to date automotive base platform, providing ride and handling commensurate with today's demands whilst gaining the capability and flexibility not currently present across the market place at this size and weight. Whilst initially aimed at the Fire and Rescue Services, SC Innovation are developing other variants of the SUV 600 to meet emerging requirements in other sectors.

Α	Length	5900 mm
В	Width	2020 mm
С	Height	1840 mm
D	Track	1610 mm
Е	Wheelbase to Axle 2	2885 mm
F	Front Overhang	720 mm
G	Wheelbase to Axle 3	+1000 mm
Н	Ground Clearance	300 mm
1	Approach Angle	36°
J	Departure Angle	30°
K	Ramp Over Angle	27°
L	Box Body Length	2050 mm
М	Box Body Height	1150 mm
N	Rear Overhang	1295 mm







SUV 600 | v1.0 | 09.2015

SUV 600 Vehicle Specification

Weight (GVW)	5300 kg	
Payload	2500 kg	
Kerb weight	2800 kg	
Speed	100 mph	
Fuel range	500 miles	
Engine	3.0 litre turbocharged V6 Diesel	
Transmision	8 speed automatic	
Drive	6x6, High/low range 6x4 option	
Suspension	Independent double wishbone air adjustable	
Steering	Power assisted	
Brakes	Four-channel all terrain ABS with ventilated disc brakes	
Wading	700 mm	
Electrical system	12v DC	
Seats	4	

Options

Active rear locking differential Heavy duty towing eyes

Runflat tyres

RHD or LHD

Roof rails

Privacy glass

Auxiliary battery & split charge system

Self recovery winch

Rear tow bar

Heavy duty seat covering

Bumper monitor

Catogory 3 Airfield fire appliance

SUV 600 Fire equipment

Body	Integrated w	ntegrated water tank, pump compartment and stowage options		
Water volui	ne	500 Litres		
Stowage volume			2000 Litres	
Pump system		Godiva HPX75, high pressure booster hose		
Foam Foamlogix® foam proportioning systems				
Fire equipn	nent payload	(Additional to full 500 litre water tank, pump, hose reel, 4 crew and BA stowage)	750 kg	
Lighting			LED Lighting system	

Options

Compressed Air Foam System (CAFS) with integral foam tank

